

## P/N MS35206-306

### **Description**

Fastener Length: 3", MS35206 series screw

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS35206306

Minimum Qty (MOQ):

NSN: 5305-00-984-5686

Schedule B: 7318.15.6080

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









# P/N MS35206-306 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.750 Inches Minimum
Fastener Length:	3.000 Inches Nominal
Head Style:	Pan
Head Diameter:	0.594 Inches Minimum And 0.615 Inches Maximum
Head Height:	0.203 Inches Minimum And 0.218 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.312 Inches
Thread Quantity Per Inch:	18
Minimum Tensile Strength:	55000 Pounds Per Square Inch
Screw Material:	Steel Comp 1010 Or Steel Comp 1011 Or Steel Comp 1013
Screw Material Document And Classification:	66 Fed Std All Material Responses
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response
Thread Series Designator:	Unc

## **How to Order**

Order this machine screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/MS35206-306">https://military-fasteners.com/screws/machine+screws/MS35206-306</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.