

## P/N MS35206-323

## **Description**

Fastener Length: 9/16", Thread: 4-40, Thread Length: 9/16",

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

SKU / Model: MS35206323

Minimum Qty (MOQ): 100

NSN: 5305-00-253-7841

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









# P/N MS35206-323 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.481 Inches Minimum And 0.562 Inches Maximum
Fastener Length:	0.531 Inches Minimum And 0.562 Inches Maximum
Head Style:	Pan
Head Diameter:	0.205 Inches Minimum And 0.219 Inches Maximum
Head Height:	0.070 Inches Minimum And 0.080 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.112 Inches
Thread Quantity Per Inch:	40
Minimum Tensile Strength:	60000 Pounds Per Square Inch
Screw Material:	Steel
Screw Material Document And Classification:	Astm A108 Assn Std Single Material Response Or Qq-s-637 Fed Spec Single Material Response Or 66 Fed Std Single Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	3 Type And 9c Style

## **How to Order**

Order this machine screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/MS35206-323">https://military-fasteners.com/screws/machine+screws/MS35206-323</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.