

P/N MS35206-334

Description

Fastener Length: 1-7/8", Thread: 8-32, Thread Length: 1-7/8", pan head, cadmium

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: MS35206334

Minimum Qty (MOQ): 50

NSN: 5305-00-510-5350

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N MS35206-334 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.751 Inches Minimum And 1.875 Inches Maximum
Fastener Length:	1.813 Inches Minimum And 1.875 Inches Maximum
Head Style:	Pan
Head Diameter:	0.306 Inches Minimum And 0.322 Inches Maximum
Head Height:	0.105 Inches Minimum And 0.115 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	60000 Pounds Per Square Inch
Screw Material:	Steel
Screw Material Document And Classification:	Qq-s-634 Fed Spec Single Material Response Or Qq-s-637 Fed Spec Single Material Response Or 66 Fed Std Single Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	3 Type And 9c Style

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/MS35206-334 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/MS35206-334 and selecting the quantity you