

Description

Fastener Length: 1-1/8", Thread: 10-24, Thread Length: 63/64", pan head

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS35206338
Minimum Qty (MOQ):	50
NSN:	5305-00-145-0960
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS35206-338 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.980 Inches Minimum And 1.125 Inches Maximum
Fastener Length:	1.063 Inches Minimum And 1.125 Inches Maximum
Head Style:	Pan
Head Diameter:	0.357 Inches Minimum And 0.373 Inches Maximum
Head Height:	0.122 Inches Minimum And 0.133 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	60000 Pounds Per Square Inch
Screw Material:	Steel Comp 1010 Or Steel Comp 1011 Or Steel Comp 1013
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 2 Cl 3 Fed Spec All Treatment Responses
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	3 Type And 9c Style
Departure From Cited Designator:	As Mod By Matl

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35206-338> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.