

Description

Fastener Length: 9/16", Thread: 1/4-20, Thread Length: 9/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS35206343 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-00-187-9874 |
| Schedule B: | 7318.15.4000 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N MS35206-343 Specifications

| | |
|---|---|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.431 Inches Minimum And 0.562 Inches Maximum |
| Fastener Length: | 0.531 Inches Minimum And 0.562 Inches Maximum |
| Head Style: | Pan |
| Head Diameter: | 0.473 Inches Minimum And 0.492 Inches Maximum |
| Head Height: | 0.162 Inches Minimum And 0.175 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.250 Inches |
| Thread Quantity Per Inch: | 20 |
| Minimum Tensile Strength: | 60000 Pounds Per Square Inch |
| Screw Material: | Steel |
| Screw Material Document And Classification: | Qq-s-634 Fed Spec Single Material Response Or Qq-s-637 Fed Spec Single Material Response Or 66 Fed Std Single Material Response |
| Screw Surface Treatment: | Cadmium And Chromate |
| Screw Surface Treatment Document And Classification: | Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response |
| Thread Series Designator: | Unc |
| Nondefinitive Spec/std Data: | 3 Type And 9c Style |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35206-343> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.