

P/N MS35206-362

Description

pan head, philips rec, MS35206

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS35206362

Minimum Qty (MOQ): 25

NSN: 5305-01-467-8214

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N MS35206-362 Specifications

| Thread Class: | 2a |
|--|--|
| Thread Direction: | Right-hand |
| Thread Length: | 1.750 Inches Nominal |
| Fastener Length: | 1.750 Inches Nominal |
| Head Style: | Pan |
| Head Diameter: | 0.256 Inches Minimum And 0.270 Inches Maximum |
| Head Height: | 0.087 Inches Minimum And 0.097 Inches Maximum |
| Internal Drive Style: | Cross Recess Type Iii |
| Nominal Thread Diameter: | 0.138 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 60000 Pounds Per Square Inch |
| Screw Material: | Steel |
| Screw Surface Treatment: | Cadmium |
| Screw Surface Treatment Document And Classification: | Qq-p-416,typeii,class3 Fed Spec 1st Treatment Response |
| Special Features: | Threads Shall Be In Accordance With Fed-std-h28/2 And Fed-std-h28/20,system21; Recess Shallbe In Accordance With Ms9006; Head Radius 0.150 |
| Thread Series Designator: | Unc |

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/MS35206-362 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.