

**Description**

Fastener Length: 1/8", Thread: 2-64, Thread Length: 1/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS35207201
Minimum Qty (MOQ):	35 EA
NSN:	5305-00-964-0792
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N MS35207-201 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.063 Inches Minimum And 0.125 Inches Maximum
<b>Fastener Length:</b>	0.094 Inches Minimum And 0.125 Inches Maximum
<b>Head Style:</b>	Pan
<b>Head Diameter:</b>	0.155 Inches Minimum And 0.167 Inches Maximum
<b>Head Height:</b>	0.053 Inches Minimum And 0.062 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.086 Inches
<b>Thread Quantity Per Inch:</b>	64
<b>Minimum Tensile Strength:</b>	60000 Pounds Per Square Inch
<b>Screw Material:</b>	Steel Comp 1010 Or Steel Comp 1011 Or Steel Comp 1013
<b>Screw Surface Treatment:</b>	Cadmium And Chromate
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses
<b>Thread Series Designator:</b>	Unf
<b>Nondefinitive Spec/std Data:</b>	3 Type And 9c Style

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35207-201> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.