

## P/N MS35207-201

### **Description**

Fastener Length: 1/8", Thread: 2-64, Thread Length: 1/8"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS35207201

Minimum Qty (MOQ): 35 EA

NSN: 5305-00-964-0792

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS35207-201 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.063 Inches Minimum And 0.125 Inches Maximum
Fastener Length:	0.094 Inches Minimum And 0.125 Inches Maximum
Head Style:	Pan
Head Diameter:	0.155 Inches Minimum And 0.167 Inches Maximum
Head Height:	0.053 Inches Minimum And 0.062 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.086 Inches
Thread Quantity Per Inch:	64
Minimum Tensile Strength:	60000 Pounds Per Square Inch
Screw Material:	Steel Comp 1010 Or Steel Comp 1011 Or Steel Comp 1013
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses
Thread Series Designator:	Unf
Nondefinitive Spec/std Data:	3 Type And 9c Style

## **How to Order**

Order this screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/MS35207-201">https://military-fasteners.com/screws/machine+screws/MS35207-201</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.