

Description

Fastener Length: 7/8", Thread: 4-48, Thread Length: 7/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS35207220
Minimum Qty (MOQ):	75 EA
NSN:	5305-00-958-0658
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS35207-220 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.833 Inches Minimum And 0.875 Inches Maximum
Fastener Length:	0.875 Inches Nominal
Head Style:	Pan
Head Diameter:	0.205 Inches Minimum And 0.219 Inches Maximum
Head Height:	0.070 Inches Minimum And 0.080 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.112 Inches
Thread Quantity Per Inch:	48
Minimum Tensile Strength:	55000 Pounds Per Square Inch
Screw Material Document And Classification:	66 Fed Std All Material Responses
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response
Thread Series Designator:	Unf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35207-220> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.