

**Description**

length: 1/2", thread: 1/4-28, pan head, cadmium plated carbon steel, fine thread, MS35207 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                                           |
|-------------------------|-------------------------------------------|
| SKU / Model:            | MS35207279                                |
| Minimum Qty (MOQ):      | 100                                       |
| NSN:                    | 5305-00-993-2463                          |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



## P/N MS35207-279 Specifications

|                                                             |                                                       |
|-------------------------------------------------------------|-------------------------------------------------------|
| <b>Thread Class:</b>                                        | 2a                                                    |
| <b>Thread Direction:</b>                                    | Right-hand                                            |
| <b>Thread Length:</b>                                       | 0.429 Inches Minimum And 0.500 Inches Maximum         |
| <b>Fastener Length:</b>                                     | 0.500 Inches Nominal                                  |
| <b>Head Style:</b>                                          | Pan                                                   |
| <b>Head Diameter:</b>                                       | 0.473 Inches Minimum And 0.492 Inches Maximum         |
| <b>Head Height:</b>                                         | 0.162 Inches Minimum And 0.175 Inches Maximum         |
| <b>Internal Drive Style:</b>                                | Cross Recess Type 1                                   |
| <b>Nominal Thread Diameter:</b>                             | 0.250 Inches                                          |
| <b>Thread Quantity Per Inch:</b>                            | 28                                                    |
| <b>Minimum Tensile Strength:</b>                            | 55000 Pounds Per Square Inch                          |
| <b>Screw Material:</b>                                      | Steel Comp 1010 Or Steel Comp 1011 Or Steel Comp 1013 |
| <b>Screw Material Document And Classification:</b>          | 66 Fed Std All Material Responses                     |
| <b>Screw Surface Treatment:</b>                             | Cadmium And Chromate                                  |
| <b>Screw Surface Treatment Document And Classification:</b> | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response |
| <b>Thread Series Designator:</b>                            | Unf                                                   |

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35207-279> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.