

## P/N MS35207-299

### **Description**

Fastener Length: 1-1/4", Thread: 1/4-24, Thread Length: 1-1/4"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS35207299

Minimum Qty (MOQ): 10 EA

NSN: 5305-00-958-0606

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS35207-299 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.167 Inches Minimum And 1.250 Inches Maximum
Fastener Length:	1.250 Inches Nominal
Head Style:	Pan
Head Diameter:	0.594 Inches Minimum And 0.615 Inches Maximum
Head Height:	0.203 Inches Minimum And 0.218 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.312 Inches
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	55000 Pounds Per Square Inch
Screw Material:	Steel Comp 1010 Or Steel Comp 1011 Or Steel Comp 1013
Screw Material Document And Classification:	66 Fed Std All Material Responses
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response
Thread Series Designator:	Unf

## **How to Order**

Order this screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/MS35207-299">https://military-fasteners.com/screws/machine+screws/MS35207-299</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.