

Description

length: 3/4", thread: 4-40, pan head, black brass, coarse thread

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS3521418
Minimum Qty (MOQ):	100
NSN:	5305-00-059-8243
ECCN:	EAR99
National Motor Freight:	096630, Screws Noi Brass / Bronze / Copper



* See page 2 for technical characteristics

P/N MS35214-18 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.700 Inches Minimum And 0.750 Inches Maximum
Fastener Length:	0.750 Inches Nominal
Head Style:	Pan
Head Diameter:	0.205 Inches Minimum And 0.219 Inches Maximum
Head Height:	0.070 Inches Minimum And 0.080 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
End Item Identification:	W/s:aircraft, Hercules C-130; Airborne Mobile Dir Air Spt Ctl (2id), (02m Jul83)(an/uyq-3a); Aircraft, Hawkeye E-2c; Aircraft, Viking S-3b; Aircraft, B-2 Bomber (atb); Osprey Class Mhc; Aircraft, Stratofortress B-52; Avenger Class Mcm; Tactical Air Opns Module (an/tyq-(23))
Nominal Thread Diameter:	0.112 Inches
Thread Quantity Per Inch:	40
Minimum Tensile Strength:	57000 Pounds Per Square Inch
Screw Material:	Copper Alloy
Screw Material Document And Classification:	Qq-b-626 Fed Spec Single Material Response Or Qq-w-321 Fed Spec Single Material Response
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35214-18> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.