

Description

length: 1/4", thread: 6-32, pan head, black brass, coarse thread

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS3521423
Minimum Qty (MOQ):	100
NSN:	5305-00-059-8248
ECCN:	EAR99
National Motor Freight:	096630, Screws Noi Brass / Bronze / Copper



P/N MS35214-23 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.188 Inches Minimum And 0.250 Inches Maximum
Fastener Length:	0.219 Inches Minimum And 0.250 Inches Maximum
Head Style:	Pan
Head Diameter:	0.256 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.087 Inches Minimum And 0.097 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
End Item Identification:	W/s:mk 28, 5-inch 38 Caliber Twin Gun Mount; Helicopter, Mh-53e; Deep Submergence Systems Programs (dssp); Landing Craft, Utility, 115 Ft; Helicopter, Search And Rescue, Hh-60h; Helicopter, Uscg Search And Rescue, Hh-60j; Fire Pumps; Aircraft (ac-130h, Mc-130h, Ec-130e, Hc-130); Helicopter, Carrier Based Asw, Sh-60f
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	57000 Pounds Per Square Inch
Screw Material:	Copper Alloy
Screw Material Document And Classification:	Qq-b-626 Fed Spec Single Material Response Or Qq-w-321 Fed Spec Single Material Response
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35214-23> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.