

# P/N MS35214-24

## **Description**

length: 5/16", thread: 6-32, pan head, black brass, coarse thread

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

SKU / Model: MS3521424

Minimum Qty (MOQ): 100

NSN: 5305-00-059-8249

ECCN: EAR99

National Motor Freight: 096630, Screws Noi Brass / Bronze / Copper









<sup>\*</sup> See page 2 for technical characteristics

# P/N MS35214-24 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.250 Inches Minimum And 0.312 Inches Maximum
Fastener Length:	0.312 Inches Nominal
Head Style:	Pan
Head Diameter:	0.256 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.087 Inches Minimum And 0.097 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	57000 Pounds Per Square Inch
Screw Material:	Copper Alloy
Screw Material Document And Classification:	Qq-b-626 Fed Spec Single Material Response Or Qq-w-321 Fed Spec Single Material Response
Thread Series Designator:	Unc

## **How to Order**

Order this machine screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/MS35214-24">https://military-fasteners.com/screws/machine+screws/MS35214-24</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.