

P/N MS35214-28

Description

length: 5/8", thread: 6-32, pan head, black brass, coarse thread

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: MS3521428

Minimum Qty (MOQ): 100

NSN: 5305-00-638-0502

ECCN: EAR99

National Motor Freight: 096630, Screws Noi Brass / Bronze / Copper









^{*} See page 2 for technical characteristics

P/N MS35214-28 Specifications

| Thread Class: | 2a |
|---------------------------------------------|------------------------------------------------------------------------------------------|
| Thread Direction: | Right-hand |
| Thread Length: | 0.562 Inches Minimum And 0.625 Inches Maximum |
| Fastener Length: | 0.625 Inches Nominal |
| Head Style: | Pan |
| Head Diameter: | 0.256 Inches Minimum And 0.270 Inches Maximum |
| Head Height: | 0.087 Inches Minimum And 0.097 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.138 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 57000 Pounds Per Square Inch |
| Screw Material: | Copper Alloy |
| Screw Material Document And Classification: | Qq-b-626 Fed Spec Single Material Response Or Qq-w-321 Fed Spec Single Material Response |
| Thread Series Designator: | Unc |

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/MS35214-28 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/MS35214-28 and selecting the quantity you