



Military-Fasteners.com

P/N MS35214-38

## Description

Fastener Length: 1/4", Thread: 8-32, Thread Length: 1/4

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	MS3521438
Minimum Qty (MOQ):	50
NSN:	5305-00-059-8263
Schedule B:	7415.33.8050
ECCN:	EAR99
National Motor Freight:	096630, Screws Noi Brass / Bronze / Copper



\* See page 2 for technical characteristics

## P/N MS35214-38 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.188 Inches Minimum And 0.250 Inches Maximum
<b>Fastener Length:</b>	0.219 Inches Minimum And 0.250 Inches Maximum
<b>Head Style:</b>	Pan
<b>Head Diameter:</b>	0.306 Inches Minimum And 0.322 Inches Maximum
<b>Head Height:</b>	0.105 Inches Minimum And 0.115 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>End Item Identification:</b>	W/s:armored Security Vehicle, Model Xm1117; Radar Set, Firefinder (an/tpq-36); Los Angeles Class Ssn (688); Main Feed Pumps; Aircraft, Hercules C-130; Ticonderoga Class Cg (47); Generator, 10kw, Diesel, Military Standard Family; Sturgeon Class Ssn (637); Helicopter, Advance Attack, Ah-1w; Landing Craft, Utility, 115 Ft
<b>Nominal Thread Diameter:</b>	0.164 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	57000 Pounds Per Square Inch
<b>Screw Material:</b>	Copper Alloy
<b>Screw Material Document And Classification:</b>	Qq-b-626 Fed Spec Single Material Response Or Qq-w-321 Fed Spec Single Material Response
<b>Thread Series Designator:</b>	Unc

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35214-38> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.