

Description

Fastener Length: 1/4", Thread: 8-32, Thread Length: 1/4

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS3521438
Minimum Qty (MOQ):	50
NSN:	5305-00-059-8263
Schedule B:	7415.33.8050
ECCN:	EAR99
National Motor Freight:	096630, Screws Noi Brass / Bronze / Copper

NO IMAGE
AVAILABLE

P/N MS35214-38 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.188 Inches Minimum And 0.250 Inches Maximum
Fastener Length:	0.219 Inches Minimum And 0.250 Inches Maximum
Head Style:	Pan
Head Diameter:	0.306 Inches Minimum And 0.322 Inches Maximum
Head Height:	0.105 Inches Minimum And 0.115 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
End Item Identification:	W/s:armored Security Vehicle, Model Xm1117; Radar Set, Firefinder (an/tpq-36); Los Angeles Class Ssn (688); Main Feed Pumps; Aircraft, Hercules C-130; Ticonderoga Class Cg (47); Generator, 10kw, Diesel, Military Standard Family; Sturgeon Class Ssn (637); Helicopter, Advance Attack, Ah-1w; Landing Craft, Utility, 115 Ft
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	57000 Pounds Per Square Inch
Screw Material:	Copper Alloy
Screw Material Document And Classification:	Qq-b-626 Fed Spec Single Material Response Or Qq-w-321 Fed Spec Single Material Response
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35214-38> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.