

Description

MS35214-39 Machine Screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--|
| SKU / Model: | MS3521439 |
| Minimum Qty (MOQ): | 50 |
| NSN: | 5305-00-059-8264 |
| ECCN: | EAR99 |
| National Motor Freight: | 096630, Screws Noi Brass / Bronze / Copper |



* See page 2 for technical characteristics

P/N MS35214-39 Specifications

| | |
|--|--|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.312 Inches Maximum |
| Fastener Length: | 0.312 Inches Nominal |
| Head Style: | Pan |
| Head Diameter: | 0.306 Inches Minimum And 0.322 Inches Maximum |
| Head Height: | 0.105 Inches Minimum And 0.115 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| End Item Identification: | W/s:fms-lst 511-1152 Class; Support Equipment, B-1 Aircraft; Torpedo Systems, Mk 46; Fms-build Figates Class Ships; Nimitz Class Cvn; An/tsq-71b Landing Control Central; Support Equipment, Mx Peacekeeper Missile; Forrestal Class Cv; Aircraft, Stratolifter C-135; Strategic Weapon Systems (poseidon And Trident) |
| Nominal Thread Diameter: | 0.164 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 57000 Pounds Per Square Inch |
| Screw Material: | Copper Alloy |
| Screw Material Document And Classification: | Qq-b-626 Fed Spec Single Material Response Or Qq-w-321 Fed Spec Single Material Response |
| Thread Series Designator: | Unc |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35214-39> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.