

P/N MS35214-4

Description

length: 5/16", thread: 2-56, pan head, black brass, coarse thread, MS35214 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS352144

Minimum Qty (MOQ): 10

NSN: 5305-00-059-8229


ECCN: EAR99

National Motor Freight: 096630, Screws Noi Brass / Bronze / Copper









^{*} See page 2 for technical characteristics

P/N MS35214-4 Specifications

Thursd Class	2-
Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.276 Inches Minimum And 0.312 Inches Maximum
Fastener Length:	0.281 Inches Minimum And 0.312 Inches Maximum
Head Style:	Pan
Head Diameter:	0.155 Inches Minimum And 0.167 Inches Maximum
Head Height:	0.053 Inches Minimum And 0.062 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
End Item Identification:	W/s:aircraft, Starlifter C-141; Fms-lst 511-1152 Class; Aircraft, Tomcat F-14; Tactical Air Opns Module (an/tyq-(23)); Aircraft, Awacs, E-3a; Airborne Mobile Dir Air Spt Ctl (2id),(02m Jul83)(an/uyq-3a); Aircraft, B-2 Bomber (atb); Helicopter, Seahawk, H-60; Radio An/grc-171b(v)4; Aircraft, Hercules C-130
Nominal Thread Diameter:	0.086 Inches
Thread Quantity Per Inch:	56
Minimum Tensile Strength:	57000 Pounds Per Square Inch
Screw Material:	Copper Alloy
Screw Material Document And Classification:	Qq-b-626 Fed Spec Single Material Response Or Qq-w-321 Fed Spec Single Material Response
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	3 Type And 9c Style

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/MS35214-4 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outher to complete your order.