

## P/N MS35214-55

### **Description**

length: 1/2", thread: 10-32, pan head machine screw - black brass - coarse thread

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS3521455

Minimum Qty (MOQ): 25

NSN: 5305-00-059-8280

ECCN: EAR99

National Motor Freight: 096630, Screws Noi Brass / Bronze / Copper



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS35214-55 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.417 Inches Minimum And 0.500 Inches Maximum
Fastener Length:	0.500 Inches Nominal
Head Style:	Pan
Head Diameter:	0.357 Inches Minimum And 0.373 Inches Maximum
Head Height:	0.122 Inches Minimum And 0.133 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
End Item Identification:	Yw/s:fire Pumps; Spruance Class Dd (963); Landing Craft, Utiity, 115 Ft; Lighter Amphibious Sp, 60-ton, Larc-Ix; Arleight Burke Class Ddg; Nimitz Class Cvn; Forrestal Class Cv; Gun, 5-in./54 Cal, Mk-42 & 45; Ticonderoga Class Cg (47)
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	57000 Pounds Per Square Inch
Screw Material:	Copper Alloy
Screw Material Document And Classification:	Qq-b-626 Fed Spec Single Material Response Or Qq-w-321 Fed Spec Single Material Response
Bearing Surface Of Head Surface Treatment:	Oxide
Color:	Black
Thread Series Designator:	Unc

## **How to Order**

Order this machine screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/MS35214-55">https://military-fasteners.com/screws/machine+screws/MS35214-55</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.