

**Description**

length: 1/2", thread: 10-32, pan head machine screw - black brass - coarse thread

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |  |
|-------------------------|--|
| SKU / Model:            | MS3521455                                  |
| Minimum Qty (MOQ):      | 25   |
| NSN:                    | 5305-00-059-8280                           |
| ECCN:                   | EAR99                                      |
| National Motor Freight: | 096630, Screws Noi Brass / Bronze / Copper |

NO IMAGE  
AVAILABLE

## P/N MS35214-55 Specifications

|  |   |
|--|---|
| <b>Thread Class:</b>                               | 2a  |
| <b>Thread Direction:</b>                           | Right-hand  |
| <b>Thread Length:</b>                              | 0.417 Inches Minimum And 0.500 Inches Maximum   |
| <b>Fastener Length:</b>                            | 0.500 Inches Nominal  |
| <b>Head Style:</b>                                 | Pan   |
| <b>Head Diameter:</b>                              | 0.357 Inches Minimum And 0.373 Inches Maximum   |
| <b>Head Height:</b>                                | 0.122 Inches Minimum And 0.133 Inches Maximum   |
| <b>Internal Drive Style:</b>                       | Cross Recess Type 1   |
| <b>End Item Identification:</b>                    | Yw/s:fire Pumps; Spruance Class Dd (963); Landing Craft, Utility, 115 Ft; Lighter Amphibious Sp, 60-ton, Larc-Ix; Arleigh Burke Class Ddg; Nimitz Class Cvn; Forrestal Class Cv; Gun, 5-in./54 Cal, Mk-42 & 45; Ticonderoga Class Cg (47) |
| <b>Nominal Thread Diameter:</b>                    | 0.190 Inches  |
| <b>Thread Quantity Per Inch:</b>                   | 24  |
| <b>Minimum Tensile Strength:</b>                   | 57000 Pounds Per Square Inch  |
| <b>Screw Material:</b>                             | Copper Alloy  |
| <b>Screw Material Document And Classification:</b> | Qq-b-626 Fed Spec Single Material Response Or Qq-w-321 Fed Spec Single Material Response  |
| <b>Bearing Surface Of Head Surface Treatment:</b>  | Oxide   |
| <b>Color:</b>                                      | Black   |
| <b>Thread Series Designator:</b>                   | Unc   |

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35214-55> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.