

## Description

length: 1/2", thread: 10-32, pan head machine screw - black brass - coarse thread

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	MS3521455
Minimum Qty (MOQ):	25
NSN:	5305-00-059-8280
ECCN:	EAR99
National Motor Freight:	096630, Screws Noi Brass / Bronze / Copper



## P/N MS35214-55 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.417 Inches Minimum And 0.500 Inches Maximum
<b>Fastener Length:</b>	0.500 Inches Nominal
<b>Head Style:</b>	Pan
<b>Head Diameter:</b>	0.357 Inches Minimum And 0.373 Inches Maximum
<b>Head Height:</b>	0.122 Inches Minimum And 0.133 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>End Item Identification:</b>	Yw/s:fire Pumps; Spruance Class Dd (963); Landing Craft, Utility, 115 Ft; Lighter Amphibious Sp, 60-ton, Larc-Ix; Arleigh Burke Class Ddg; Nimitz Class Cvn; Forrestal Class Cv; Gun, 5-in./54 Cal, Mk-42 & 45; Ticonderoga Class Cg (47)
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Thread Quantity Per Inch:</b>	24
<b>Minimum Tensile Strength:</b>	57000 Pounds Per Square Inch
<b>Screw Material:</b>	Copper Alloy
<b>Screw Material Document And Classification:</b>	Qq-b-626 Fed Spec Single Material Response Or Qq-w-321 Fed Spec Single Material Response
<b>Bearing Surface Of Head Surface Treatment:</b>	Oxide
<b>Color:</b>	Black
<b>Thread Series Designator:</b>	Unc

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35214-55> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.