

Description

length: 1/2", thread: 10-32, pan head machine screw - black brass - coarse thread

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS3521455
Minimum Qty (MOQ):	25
NSN:	5305-00-059-8280
ECCN:	EAR99
National Motor Freight:	096630, Screws Noi Brass / Bronze / Copper

NO IMAGE
AVAILABLE

P/N MS35214-55 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.417 Inches Minimum And 0.500 Inches Maximum
Fastener Length:	0.500 Inches Nominal
Head Style:	Pan
Head Diameter:	0.357 Inches Minimum And 0.373 Inches Maximum
Head Height:	0.122 Inches Minimum And 0.133 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
End Item Identification:	Yw/s:fire Pumps; Spruance Class Dd (963); Landing Craft, Utility, 115 Ft; Lighter Amphibious Sp, 60-ton, Larc-Ix; Arleigh Burke Class Ddg; Nimitz Class Cvn; Forrestal Class Cv; Gun, 5-in./54 Cal, Mk-42 & 45; Ticonderoga Class Cg (47)
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	57000 Pounds Per Square Inch
Screw Material:	Copper Alloy
Screw Material Document And Classification:	Qq-b-626 Fed Spec Single Material Response Or Qq-w-321 Fed Spec Single Material Response
Bearing Surface Of Head Surface Treatment:	Oxide
Color:	Black
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35214-55> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.