

Description

Fastener Length: 7/16", Thread: 2-56, Thread Length: 13/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--|
| SKU / Model: | MS352146 |
| Minimum Qty (MOQ): | 15 EA |
| NSN: | 5305-00-806-5219 |
| Schedule B: | 7415.33.8050 |
| ECCN: | EAR99 |
| National Motor Freight: | 096630, Screws Noi Brass / Bronze / Copper |

NO IMAGE
AVAILABLE

P/N MS35214-6 Specifications

| | |
|---|--|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.402 Inches Minimum And 0.438 Inches Maximum |
| Fastener Length: | 0.438 Inches Nominal |
| Head Style: | Pan |
| Head Diameter: | 0.155 Inches Minimum And 0.167 Inches Maximum |
| Head Height: | 0.053 Inches Minimum And 0.062 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.086 Inches |
| Thread Quantity Per Inch: | 56 |
| Minimum Tensile Strength: | 57000 Pounds Per Square Inch |
| Screw Material: | Copper Alloy |
| Screw Material Document And Classification: | Qq-b-626 Fed Spec Single Material Response Or Qq-w-321 Fed Spec Single Material Response |
| Screw Surface Treatment: | Cadmium And Chromate |
| Screw Surface Treatment Document And Classification: | Qq-b-416,ty 2,cl 3 Fed Spec All Treatment Responses |
| Thread Series Designator: | Unc |
| Departure From Cited Designator: | As Modified By Surface Treatment |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35214-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.