



Military-Fasteners.com

P/N MS35214-7

Description

Fastener Length: 1/2", Thread: 2-56, Thread Length: 15/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS352147
Minimum Qty (MOQ):	75 EA
NSN:	5305-00-840-3956
Schedule B:	7415.33.8050
ECCN:	EAR99
National Motor Freight:	096630, Screws Noi Brass / Bronze / Copper



* See page 2 for technical characteristics

P/N MS35214-7 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.464 Inches Minimum And 0.500 Inches Maximum
Fastener Length:	0.500 Inches Nominal
Head Style:	Pan
Head Diameter:	0.155 Inches Minimum And 0.167 Inches Maximum
Head Height:	0.053 Inches Minimum And 0.062 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
End Item Identification:	10f;75f;jrn;19f;20n;58n;yga;jzn;04f;02f
Nominal Thread Diameter:	0.086 Inches
Thread Quantity Per Inch:	56
Minimum Tensile Strength:	57000 Pounds Per Square Inch
Screw Material:	Copper Alloy
Screw Material Document And Classification:	Qq-b-626 Fed Spec Single Material Response Or Qq-w-321 Fed Spec Single Material Response
Thread Series Designator:	Unc

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35214-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.