



Military-Fasteners.com

**P/N MS35214-99**

## Description

Fastener Length: 1-1/2", Thread: 3/8-16, Thread Length: 1-3/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	MS3521499
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-954-9548
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	096630, Screws Noi Brass / Bronze / Copper



\* See page 2 for technical characteristics

## P/N MS35214-99 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	1.375 Inches Minimum And 1.500 Inches Maximum
<b>Fastener Length:</b>	1.500 Inches Nominal
<b>Head Style:</b>	Pan
<b>Head Diameter:</b>	0.716 Inches Minimum And 0.740 Inches Maximum
<b>Head Height:</b>	0.244 Inches Minimum And 0.261 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.375 Inches
<b>Thread Quantity Per Inch:</b>	16
<b>Minimum Tensile Strength:</b>	57000 Pounds Per Square Inch
<b>Screw Material:</b>	Copper Alloy
<b>Screw Material Document And Classification:</b>	Qq-b-626 Fed Spec Single Material Response Or Qq-w-321 Fed Spec Single Material Response
<b>Screw Surface Treatment:</b>	Oxide
<b>Screw Surface Treatment Document And Classification:</b>	Mil-f-495 Mil Std Single Treatment Response
<b>Thread Series Designator:</b>	Unc

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35214-99> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.