

Description

Fastener Length: 3/8", Thread: 4-48, Thread Length: 3/8", MS35215 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS3521514
Minimum Qty (MOQ):	10
NSN:	5305-00-954-8122
Schedule B:	7415.33.8050
ECCN:	9A991
National Motor Freight:	096630, Screws Noi Brass / Bronze / Copper



P/N MS35215-14 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.333 Inches Minimum And 0.375 Inches Maximum
Fastener Length:	0.375 Inches Nominal
Head Style:	Pan
Head Diameter:	0.205 Inches Minimum And 0.219 Inches Maximum
Head Height:	0.070 Inches Minimum And 0.080 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.112 Inches
Thread Quantity Per Inch:	48
Minimum Tensile Strength:	57000 Pounds Per Square Inch
Screw Material:	Copper Alloy
Screw Material Document And Classification:	Qq-b-626 Fed Spec Single Material Response Or Qq-w-321 Fed Spec Single Material Response
Thread Series Designator:	Unf

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35215-14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.