

P/N MS35215-62

Description

Fastener Length: 1-3/4", Thread: 10-32, Thread Length: 1-3/4",

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	MS3521562
Minimum Qty (MOQ):	5
NSN:	5305-00-059-8392
Schedule B:	7415.33.8050
ECCN:	EAR99
National Motor Freight:	096630, Screws Noi Brass / Bronze / Copper



^{*} See page 2 for technical characteristics

P/N MS35215-62 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.688 Inches Minimum And 1.750 Inches Maximum
Fastener Length:	1.750 Inches Nominal
Head Style:	Pan
Head Diameter:	0.357 Inches Minimum And 0.373 Inches Maximum
Head Height:	0.122 Inches Minimum And 0.133 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	57000 Pounds Per Square Inch
Screw Material:	Copper Alloy
Screw Material Document And Classification:	Qq-b-626 Fed Spec Single Material Response Or Qq-w-321 Fed Spec Single Material Response
Thread Series Designator:	Unf

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/MS35215-62 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.