

Description

Fastener Length: 3/8", Thread: 6-32, Thread Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---------------------|
| SKU / Model: | MS3521825 |
| Minimum Qty (MOQ): | 15 EA |
| NSN: | 5305-00-059-8668 |
| Schedule B: | 7616.10.9090 |
| ECCN: | 9A991 |
| National Motor Freight: | 013680, Alum Screws |

NO IMAGE
AVAILABLE

P/N MS35218-25 Specifications

| | |
|---|---|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.313 Inches Minimum And 0.375 Inches Maximum |
| Fastener Length: | 0.375 Inches Nominal |
| Head Style: | Pan |
| Head Diameter: | 0.256 Inches Minimum And 0.270 Inches Maximum |
| Head Height: | 0.087 Inches Minimum And 0.097 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.138 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 62000 Pounds Per Square Inch |
| Screw Material: | Aluminum Alloy 2024 |
| Screw Material Document And Classification: | Qq-a-225/6 Fed Spec Single Material Response |
| Screw Surface Treatment: | Anodize |
| Screw Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec Single Treatment Response |
| Thread Series Designator: | Unc |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35218-25> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.