

**Description**

Fastener Length: 7/16", Thread: 6-32, Thread Length: 7/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS3521826                                 |
| Minimum Qty (MOQ):      | 25 EA                                     |
| NSN:                    | 5305-00-939-0795                          |
| Schedule B:             | 7616.10.9090                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N MS35218-26 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>  | 2a  |
| <b>Thread Direction:</b>                                    | Right-hand                                    |
| <b>Thread Length:</b>                                       | 0.376 Inches Minimum And 0.438 Inches Maximum |
| <b>Fastener Length:</b>                                     | 0.438 Inches Nominal                          |
| <b>Head Style:</b>  | Pan   |
| <b>Head Diameter:</b>                                       | 0.256 Inches Minimum And 0.270 Inches Maximum |
| <b>Head Height:</b>   | 0.087 Inches Minimum And 0.097 Inches Maximum |
| <b>Internal Drive Style:</b>                                | Cross Recess Type 1                           |
| <b>Nominal Thread Diameter:</b>                             | 0.138 Inches                                  |
| <b>Thread Quantity Per Inch:</b>                            | 32  |
| <b>Minimum Tensile Strength:</b>                            | 62000 Pounds Per Square Inch                  |
| <b>Screw Material:</b>                                      | Aluminum Alloy 2024                           |
| <b>Screw Material Document And Classification:</b>          | Qq-a-225/6 Fed Spec Single Material Response  |
| <b>Screw Surface Treatment:</b>                             | Anodize                                       |
| <b>Screw Surface Treatment Document And Classification:</b> | Mil-a-8625 Mil Spec Single Treatment Response |
| <b>Thread Series Designator:</b>                            | Unc   |

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35218-26> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.