

Description

Fastener Length: 7/8", Thread: 6-32, Thread Length: 7/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS3521830
Minimum Qty (MOQ):	15 EA
NSN:	5305-00-059-8673
Schedule B:	7616.10.9090
ECCN:	EAR99
National Motor Freight:	013680, Alum Screws

NO IMAGE
AVAILABLE

P/N MS35218-30 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.813 Inches Minimum And 0.875 Inches Maximum
Fastener Length:	0.875 Inches Nominal
Head Style:	Pan
Head Diameter:	0.256 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.087 Inches Minimum And 0.097 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	62000 Pounds Per Square Inch
Screw Material:	Aluminum Alloy 2024
Screw Material Document And Classification:	Qq-a-225/6 Fed Spec Single Material Response
Screw Surface Treatment:	Anodize
Screw Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response
Thread Series Designator:	Unc

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35218-30> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.