

Description

Fastener Length: 5/16", Thread: 6-40, Thread Length: 17/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS3521924
Minimum Qty (MOQ):	25 EA
NSN:	5305-00-869-9390
Schedule B:	7616.10.9090
ECCN:	9A991
National Motor Freight:	013680, Alum Screws

NO IMAGE
AVAILABLE

P/N MS35219-24 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.262 Inches Minimum
Fastener Length:	0.312 Inches Nominal
Head Style:	Pan
Head Diameter:	0.256 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.087 Inches Minimum And 0.097 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	40
Minimum Tensile Strength:	62000 Pounds Per Square Inch
Screw Material:	Aluminum Alloy 2024 Or Aluminum Alloy 2017
Screw Material Document And Classification:	Qq-a-200/3 Fed Spec 1st Material Response Or Qq-a-225/6 Fed Spec 1st Material Response Or Qq-a-225/5 Fed Spec 2nd Material Response
Screw Surface Treatment:	Oxide Film
Screw Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec Single Treatment Response
Thread Series Designator:	Unf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35219-24> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.