

**Description**

Fastener Length: 1/2", Thread: 8-36, Thread Length: 1/2"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS3521942
Minimum Qty (MOQ):	35 EA
NSN:	5305-00-958-1005
Schedule B:	7616.10.9090
ECCN:	9A991
National Motor Freight:	013680, Alum Screws

NO IMAGE  
AVAILABLE

## P/N MS35219-42 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.444 Inches Minimum And 0.500 Inches Maximum
<b>Fastener Length:</b>	0.500 Inches Nominal
<b>Head Style:</b>	Pan
<b>Head Diameter:</b>	0.306 Inches Minimum And 0.322 Inches Maximum
<b>Head Height:</b>	0.105 Inches Minimum And 0.115 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.164 Inches
<b>Thread Quantity Per Inch:</b>	36
<b>Minimum Tensile Strength:</b>	62000 Pounds Per Square Inch
<b>Screw Material:</b>	Aluminum Alloy 2024
<b>Screw Material Document And Classification:</b>	Qq-a-225/6 Fed Spec Single Material Response
<b>Screw Surface Treatment:</b>	Anodize
<b>Screw Surface Treatment Document And Classification:</b>	Mil-a-8625 Mil Spec Single Treatment Response
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35219-42> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.