

Description

Fastener Length: 3/16", Thread: 2-64, Thread Length: 3/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS352342
Minimum Qty (MOQ):	80 EA
NSN:	5305-00-550-5000
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS35234-2 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.156 Inches Minimum And 0.188 Inches Maximum
Fastener Length:	0.156 Inches Minimum And 0.188 Inches Maximum
Head Style:	Pan No. 2
Head Diameter:	0.155 Inches Minimum And 0.167 Inches Maximum
Head Height:	0.045 Inches Minimum And 0.053 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.086 Inches
Thread Quantity Per Inch:	64
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Screw Material:	Steel Corrosion Resisting
Screw Material Document And Classification:	Qq-s-763 Fed Spec Single Material Response
Screw Surface Treatment:	Passivate
Thread Series Designator:	Unf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35234-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.