

Description

Fastener Length: 1-", Thread: 4-40, Thread Length: 59/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS3524928
Minimum Qty (MOQ):	15 EA
NSN:	5305-00-022-7064
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS35249-28 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.914 Inches Minimum And 0.933 Inches Maximum
Fastener Length:	1.000 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.200 Inches Minimum
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.112 Inches
Thread Quantity Per Inch:	40
Countersink Angle:	80.0 Degrees Minimum And 82.0 Degrees Maximum
Screw Material:	Steel Comp 410
Screw Material Document And Classification:	Qq-s-763 Fed Spec Single Material Response
Screw Surface Treatment:	Passivate
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	1 Type And 2s Style

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35249-28> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.