

**Description**

Fastener Length: 1-", Thread: 4-40, Thread Length: 59/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                                           |
|-------------------------|-------------------------------------------|
| SKU / Model:            | MS3524928                                 |
| Minimum Qty (MOQ):      | 15 EA                                     |
| NSN:                    | 5305-00-022-7064                          |
| Schedule B:             | 7318.15.6080                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N MS35249-28 Specifications

|                                                    |                                               |
|----------------------------------------------------|-----------------------------------------------|
| <b>Thread Class:</b>                               | 2a                                            |
| <b>Thread Direction:</b>                           | Right-hand                                    |
| <b>Thread Length:</b>                              | 0.914 Inches Minimum And 0.933 Inches Maximum |
| <b>Fastener Length:</b>                            | 1.000 Inches Nominal                          |
| <b>Head Style:</b>                                 | Flat Countersunk                              |
| <b>Head Diameter:</b>                              | 0.200 Inches Minimum                          |
| <b>Internal Drive Style:</b>                       | Slot                                          |
| <b>Nominal Thread Diameter:</b>                    | 0.112 Inches                                  |
| <b>Thread Quantity Per Inch:</b>                   | 40                                            |
| <b>Countersink Angle:</b>                          | 80.0 Degrees Minimum And 82.0 Degrees Maximum |
| <b>Screw Material:</b>                             | Steel Comp 410                                |
| <b>Screw Material Document And Classification:</b> | Qq-s-763 Fed Spec Single Material Response    |
| <b>Screw Surface Treatment:</b>                    | Passivate                                     |
| <b>Thread Series Designator:</b>                   | Unc                                           |
| <b>Nondefinitive Spec/std Data:</b>                | 1 Type And 2s Style                           |

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35249-28> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.