

Description

Fastener Length: 3/8", Thread: 6-32, Thread Length: 19/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS3524935
Minimum Qty (MOQ):	30 EA
NSN:	5305-00-457-5911
Schedule B:	7318.15.6080
ECCN:	9A991



* See page 2 for technical characteristics

P/N MS35249-35 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.261 Inches Minimum And 0.306 Inches Maximum
Fastener Length:	0.344 Inches Minimum And 0.375 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.249 Inches Minimum And 0.279 Inches Maximum
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Countersink Angle:	80.0 Degrees Minimum And 82.0 Degrees Maximum
Screw Material:	Steel Corrosion Resisting
Screw Material Document And Classification:	66 Fed Std Single Material Response
Screw Surface Treatment:	Passivate
Thread Series Designator:	Unc

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35249-35> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.