

Description

Fastener Length: 1/4", Thread: 10-24, Thread Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS3524967
Minimum Qty (MOQ):	15 EA
NSN:	5305-00-985-4813
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS35249-67 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.312 Inches Nominal
Fastener Length:	0.312 Inches Nominal
Head Style:	Flat Countersunk Undercut
Head Diameter:	0.348 Inches Minimum And 0.385 Inches Maximum
Head Height:	0.065 Inches Minimum And 0.083 Inches Maximum
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	24
Countersink Angle:	0.80 Degrees Minimum And 0.82 Degrees Maximum
Screw Material:	Steel Corrosion Resisting
Screw Material Document And Classification:	Qq-s-763,class And Cond A/a Fed Spec Single Material Response
Screw Surface Treatment:	Passivate
Thread Series Designator:	Unc

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35249-67> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.