

## P/N MS35265-13

### **Description**

Length: 1/4, thread: 4-40, fillister head machine screw, cadmium plated carbon steel, coarse thread

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS3526513

Minimum Qty (MOQ): 100

NSN: 5305-00-543-2024

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









<sup>\*</sup> See page 2 for technical characteristics

# P/N MS35265-13 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.200 Inches Minimum And 0.250 Inches Maximum
Fastener Length:	0.219 Inches Minimum And 0.250 Inches Maximum
Head Style:	Fillister
Head Diameter:	0.166 Inches Minimum And 0.183 Inches Maximum
Head Height:	0.072 Inches Minimum And 0.079 Inches Maximum
Hole Diameter:	0.037 Inches Nominal
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.112 Inches
Hole Quantity:	1
Thread Quantity Per Inch:	40
Minimum Tensile Strength:	60000 Pounds Per Square Inch
Screw Material:	Steel
Screw Material Document And Classification:	Qq-s-633 Fed Spec Single Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response
Head Hole Configuration Style:	Round
Thread Series Designator:	Unc

## **How to Order**

Order this machine screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/MS35265-13">https://military-fasteners.com/screws/machine+screws/MS35265-13</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.