

P/N MS35265-24

Military-Fasteners.com

#### Description

Fastener Length: 1/8", Thread: 6-32, Thread Length: 1/16", MS35265 series screw

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

SKU / Model:	MS3526524
Minimum Qty (MOQ):	10
NSN:	5305-00-721-5783
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

# P/N MS35265-24 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.089 Inches Minimum
Fastener Length:	0.125 Inches Nominal
Head Style:	Fillister
Head Diameter:	0.208 Inches Minimum And 0.226 Inches Maximum
Head Height:	0.089 Inches Minimum And 0.096 Inches Maximum
Hole Diameter:	0.031 Inches Nominal
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.138 Inches
Hole Quantity:	1
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	60000 Pounds Per Square Inch
Screw Material:	Steel
Screw Material Document And Classification:	Qq-s-631 Fed Spec Single Material Response Or Qq-s-634 Fed Spec Single Material Response Or Qq-s-637 Fed Spec Single Material Response
Screw Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response
Head Hole Configuration Style:	Round
Thread Series Designator:	Unc

## How to Order

Order this machine screw from our inventory online by visiting <u>https://military-fasteners.com/screws/machine+screws/MS35265-24</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.