

**Description**

length: 3/8", thread: 6-32, fillister head machine screw, cadmium plated carbon steel, coarse thread

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[AN500A6-6](#)

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS3526528                                 |
| Minimum Qty (MOQ):      | 50  |
| NSN:                    | 5305-00-582-5807                          |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

## P/N MS35265-28 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>  | 2a   |
| <b>Thread Direction:</b>                                    | Right-hand   |
| <b>Thread Length:</b>                                       | 0.313 Inches Minimum And 0.375 Inches Maximum              |
| <b>Fastener Length:</b>                                     | 0.375 Inches Nominal                                       |
| <b>Head Style:</b>  | Fillister  |
| <b>Head Diameter:</b>                                       | 0.208 Inches Minimum And 0.226 Inches Maximum              |
| <b>Head Height:</b>   | 0.089 Inches Minimum And 0.096 Inches Maximum              |
| <b>Hole Diameter:</b>                                       | 0.046 Inches Nominal                                       |
| <b>Internal Drive Style:</b>                                | Slot   |
| <b>Nominal Thread Diameter:</b>                             | 0.138 Inches   |
| <b>Hole Quantity:</b>                                       | 1  |
| <b>Thread Quantity Per Inch:</b>                            | 32   |
| <b>Minimum Tensile Strength:</b>                            | 55000 Pounds Per Square Inch                               |
| <b>Screw Material:</b>                                      | Steel  |
| <b>Screw Material Document And Classification:</b>          | Qq-s-633 Fed Spec Single Material Response                 |
| <b>Screw Surface Treatment:</b>                             | Cadmium And Chromate                                       |
| <b>Screw Surface Treatment Document And Classification:</b> | Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response |
| <b>Head Hole Configuration Style:</b>                       | Round  |
| <b>Thread Series Designator:</b>                            | Unc  |

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35265-28> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.