

Description

length: 7/16", thread: 6-32, fillister head machine screw, cadmium plated carbon steel, coarse thread

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS3526529 |
| Minimum Qty (MOQ): | 50 |
| NSN: | 5305-00-543-5059 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N MS35265-29 Specifications

| | |
|---|---|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.376 Inches Minimum And 0.438 Inches Maximum |
| Fastener Length: | 0.438 Inches Nominal |
| Head Style: | Fillister |
| Head Diameter: | 0.208 Inches Minimum And 0.226 Inches Maximum |
| Head Height: | 0.089 Inches Minimum And 0.096 Inches Maximum |
| Hole Diameter: | 0.046 Inches Nominal |
| Internal Drive Style: | Slot |
| Nominal Thread Diameter: | 0.138 Inches |
| Hole Quantity: | 1 |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 55000 Pounds Per Square Inch |
| Screw Material: | Steel |
| Screw Material Document And Classification: | Qq-s-633 Fed Spec Single Material Response |
| Screw Surface Treatment: | Cadmium And Chromate |
| Screw Surface Treatment Document And Classification: | Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response |
| Head Hole Configuration Style: | Round |
| Thread Series Designator: | Unc |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35265-29> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.