

**Description**

length: 1/2", thread: 6-32, fillister head machine screw, cadmium plated carbon steel, coarse thread

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS3526530
Minimum Qty (MOQ):	50
NSN:	5305-00-579-2139
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N MS35265-30 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.438 Inches Minimum
<b>Fastener Length:</b>	0.500 Inches Nominal
<b>Head Style:</b>	Fillister
<b>Head Diameter:</b>	0.208 Inches Minimum And 0.226 Inches Maximum
<b>Head Height:</b>	0.089 Inches Minimum And 0.096 Inches Maximum
<b>Hole Diameter:</b>	0.031 Inches Nominal
<b>Internal Drive Style:</b>	Slot
<b>Nominal Thread Diameter:</b>	0.138 Inches
<b>Hole Quantity:</b>	1
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	60000 Pounds Per Square Inch
<b>Screw Material:</b>	Steel
<b>Screw Surface Treatment:</b>	Cadmium And Chromate
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response
<b>Head Hole Configuration Style:</b>	Round Longitudinal Hole
<b>Thread Series Designator:</b>	Unc

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35265-30> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.