

Description

length: 5/8", thread: 6-32, fillister head, cadmium plated carbon steel, coarse thread, MS35265 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS3526531
Minimum Qty (MOQ):	50
NSN:	5305-00-582-5808
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS35265-31 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.563 Inches Minimum And 0.625 Inches Maximum
Fastener Length:	0.625 Inches Nominal
Head Style:	Fillister
Head Diameter:	0.208 Inches Minimum And 0.226 Inches Maximum
Head Height:	0.089 Inches Minimum And 0.096 Inches Maximum
Hole Diameter:	0.046 Inches Nominal
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.138 Inches
Hole Quantity:	1
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	55000 Pounds Per Square Inch
Screw Material:	Steel Comp 1013 Or Steel Comp 1015 Or Steel Comp 1016 Or Steel Comp 1017 Or Steel Comp 1018 Or Steel Comp 1019 Or Steel Comp 1020 Or Steel Comp 1022 Or Steel Comp 1524 Or Steel Comp 1025 Or Steel Comp 1527 Or Steel Comp 1030 Or Steel Comp 1033 Or Steel Comp 1034 Or Steel Comp 1038 Or Steel Comp 1040 Or Steel Comp 1541 Or Steel Comp 1108 Or Steel Comp 1109 Or Steel Comp 1110
Screw Material Document And Classification:	Qq-s-633 Fed Spec Single Material Response
Screw Surface Treatment Document And Classification:	Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response
Head Hole Configuration Style:	Round
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35265-31> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.