

Description


length: 3/8", thread: 10-24, fillister head machine screw, cadmium plated carbon steel, coarse thread

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS3526561
Minimum Qty (MOQ):	50
NSN:	5305-00-543-4662
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS35265-61 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.292 Inches Minimum
Fastener Length:	0.375 Inches Nominal
Head Style:	Fillister
Head Diameter:	0.292 Inches Minimum And 0.312 Inches Maximum
Head Height:	0.123 Inches Minimum And 0.130 Inches Maximum
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	60000 Pounds Per Square Inch
Screw Material:	Steel
Screw Material Document And Classification:	Qq-s-631 Fed Spec Single Material Response Or Qq-s-634 Fed Spec Single Material Response Or Qq-s-637 Fed Spec Single Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35265-61> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.