

Description

length: 5/8", thread: 10-24, fillister head, cadmium plated carbon steel, coarse thread, MS35265 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS3526564 |
| Minimum Qty (MOQ): | 50 |
| NSN: | 5305-00-614-0245 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N MS35265-64 Specifications

| | |
|---|--|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.542 Inches Minimum And 0.625 Inches Maximum |
| Fastener Length: | 0.625 Inches Nominal |
| Head Style: | Fillister |
| Head Diameter: | 0.292 Inches Minimum And 0.296 Inches Maximum |
| Head Height: | 0.123 Inches Minimum And 0.130 Inches Maximum |
| Hole Diameter: | 0.046 Inches Nominal |
| Internal Drive Style: | Slot |
| Nominal Thread Diameter: | 0.190 Inches |
| Hole Quantity: | 1 |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 55000 Pounds Per Square Inch |
| Screw Material: | Steel |
| Screw Material Document And Classification: | Qq-s-633 Fed Spec Single Material Response |
| Screw Surface Treatment: | Cadmium And Chromate |
| Screw Surface Treatment Document And Classification: | Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response |
| Head Hole Configuration Style: | Round Longitudinal Hole |
| Thread Series Designator: | Unc |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35265-64> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.