

P/N MS35265-8

Description

Fastener Length: 5/8", Hole Diameter: 1/32", Thread: 2-56, Thread Length: 5/8",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

National Motor Freight:

| SKU / Model: | MS352658 |
|--------------------|------------------|
| Minimum Qty (MOQ): | 25 |
| NSN: | 5305-00-616-2806 |
| Schedule B: | 7318.15.6080 |
| ECCN: | 9A991 |
| | |

093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N MS35265-8 Specifications

| Thread Class: | 2a |
|--|--|
| Thread Direction: | Right-hand |
| Thread Length: | 0.625 Inches Minimum |
| Fastener Length: | 0.625 Inches Nominal |
| Head Style: | Fillister |
| Head Diameter: | 0.124 Inches Minimum And 0.140 Inches Maximum |
| Head Height: | 0.055 Inches Minimum And 0.062 Inches Maximum |
| Hole Diameter: | 0.031 Inches Nominal |
| Internal Drive Style: | Slot |
| Nominal Thread Diameter: | 0.086 Inches |
| Hole Quantity: | 1 |
| Thread Quantity Per Inch: | 56 |
| Minimum Tensile Strength: | 60000 Pounds Per Square Inch |
| Screw Material: | Steel |
| Screw Material Document And Classification: | Qq-s-631 Fed Spec Single Material Response Or Qq-s-634 Fed Spec Single Material Response Or Qq-s-637 Fed Spec Single Material Response |
| Screw Surface Treatment: | Cadmium And Chromate |
| Screw Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response |
| Head Hole Configuration Style: | Round |
| Thread Series Designator: | Unc |

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/MS35265-8 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outher to complete your order.