

**Description**

Fastener Length: 3/16", Hole Diameter: ", Thread: 2-64, Thread Length: 3/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS352662
Minimum Qty (MOQ):	35 EA
NSN:	5305-00-182-9582
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N MS35266-2 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.126 Inches Minimum And 0.188 Inches Maximum
<b>Fastener Length:</b>	0.157 Inches Minimum And 0.188 Inches Maximum
<b>Head Style:</b>	Fillister
<b>Head Diameter:</b>	0.124 Inches Minimum And 0.140 Inches Maximum
<b>Head Height:</b>	0.055 Inches Minimum And 0.062 Inches Maximum
<b>Hole Diameter:</b>	0.031 Inches Nominal
<b>Internal Drive Style:</b>	Slot
<b>Nominal Thread Diameter:</b>	0.086 Inches
<b>Hole Quantity:</b>	1
<b>Thread Quantity Per Inch:</b>	64
<b>Minimum Tensile Strength:</b>	60000 Pounds Per Square Inch
<b>Screw Material:</b>	Steel
<b>Screw Surface Treatment:</b>	Cadmium And Chromate
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response
<b>Head Hole Configuration Style:</b>	Round
<b>Thread Series Designator:</b>	Unf
<b>Nondefinitive Spec/std Data:</b>	1 Type And 5s Style

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35266-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.