

Description

Fastener Length: 3/16", Hole Diameter: 1/32", Thread: 6-40, Thread Length: 3/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-------------------------------|
| SKU / Model: | MS3526625 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5305-00-145-0949 |
| National Motor Freight: | 096640, Screws, Iron Or Steel |

NO IMAGE
AVAILABLE

P/N MS35266-25 Specifications

| | |
|---------------------------------------|---|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.107 Inches Minimum And 0.188 Inches Maximum |
| Fastener Length: | 0.157 Inches Minimum And 0.188 Inches Maximum |
| Head Style: | Fillister |
| Head Diameter: | 0.208 Inches Minimum And 0.226 Inches Maximum |
| Head Height: | 0.089 Inches Minimum And 0.096 Inches Maximum |
| Hole Diameter: | 0.046 Inches Nominal |
| Internal Drive Style: | Slot |
| Nominal Thread Diameter: | 0.138 Inches |
| Hole Quantity: | 1 |
| Thread Quantity Per Inch: | 40 |
| Minimum Tensile Strength: | 60000 Pounds Per Square Inch |
| Screw Material: | Steel |
| Screw Surface Treatment: | Cadmium |
| Head Hole Configuration Style: | Round |
| Thread Series Designator: | Unf |
| Nondefinitive Spec/std Data: | 1 Type And 5s Style |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35266-25> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.