

Description

Fastener Length: 3/16", Hole Diameter: 1/32", Thread: 6-40, Thread Length: 3/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS3526625
Minimum Qty (MOQ):	1 EA
NSN:	5305-00-145-0949
National Motor Freight:	096640, Screws, Iron Or Steel

NO IMAGE
AVAILABLE

P/N MS35266-25 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.107 Inches Minimum And 0.188 Inches Maximum
Fastener Length:	0.157 Inches Minimum And 0.188 Inches Maximum
Head Style:	Fillister
Head Diameter:	0.208 Inches Minimum And 0.226 Inches Maximum
Head Height:	0.089 Inches Minimum And 0.096 Inches Maximum
Hole Diameter:	0.046 Inches Nominal
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.138 Inches
Hole Quantity:	1
Thread Quantity Per Inch:	40
Minimum Tensile Strength:	60000 Pounds Per Square Inch
Screw Material:	Steel
Screw Surface Treatment:	Cadmium
Head Hole Configuration Style:	Round
Thread Series Designator:	Unf
Nondefinitive Spec/std Data:	1 Type And 5s Style

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35266-25> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.